

LITHIUM BATTERY MODULE-YH12205 (12.8V205AH)

FEATURES

- HIGH ENERGY DENSITY;
- SUPERIOR GRADE A LITHIUM CELLS;
- *OVER 5000 CYCLES @ 100% DOD;
- *INTELLIGENT BMS WITH MULTIPLE PROTECTIONS ENSURES THE EXTREME SAFETY;
- *IP65 PROTECTION GRADE;
- *INCREASE CAPACITY AND VOLTAGE THROUGH PARALLEL AND SERIES CONNECTIONS;
- * UL, CE, UN38.3, IEC CERTIFICATED.



APPLICATIONS

SOLAR, RVS, OUTDOOR POWER SUPPLY, etc.



SPECIFICATION

Electrical Characteristics	Nominal voltage	12.8V
	Nominal Capacity	205Ah (0.5C,25 °C)
	Energy	2624Wh
	Internal Resistance	≤ 150mΩ
	Cycle Life	>5000 cycles@1C 100%DOD 5000 cycles@0.5C100%DOD
	Months Self Discharge	<3%
	Efficiency of charge	100% @0.2C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	14.6 ± 0.2V
	Charge Mode	0.2C to 14.6V, then 14.6V,charge current 0.02C(CC/CV)
	Charge Current	50A
	Max Charge Current	200A
	Charge Cut-off Voltage	14.8V ± 0.2V
Standard Discharge	Continuous Current	200A
	Max. Pulse Current	210A(<3s)
	Discharge cut-off voltage	10.8V
Environmental	Charge Temperature	0 °C to 45 °C (32F to 113F) @60 ± 25% Relative Humidity
	Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60 ± 25% Relative Humidity
	Storage Temperature	0 °C to 40 °C (32F to 104F) @60 ± 25% Relative Humidity
Mechanical	Cell & Method	3.2V205AH-4S1P
	Plastic Case	ABS
	Dimensions (in./mm.)	387*206*273 mm
	Weight (lbs./kg.)	21Kg
	Terminal	M8
	Color	Black